



## 16AX 250V 1Gang, 1-Way Switch

Code: S5124

### Main

Product Or Component Type	Switch
Device Application	Control
Additional Switch Application	On/off switching
Number Of Rocker	1
Switch Function	1-way
Color Tint	White, Beige, Champagne, Grey, Black

### Complementary

Technology Type	Electromechanical
Device Presentation	Complete mechanism
Actuator	Rocker
Number Of Gangs	1 gang
Material	PC (Polycarbonate): Frame Cover PC (Polycarbonate): Base PA6: Actuator Brass and copper alloy: terminals Silver alloy: contacts
Surface Finish	Glossy
Surface Treatment	Untreated
[Ue] Rated Operational Voltage	220...250 V
Type Of Packing	Plastic bag
Network Type	AC
Quantity Per Set	1
Sale Per Indivisible Quantity	1
Rated Current	16 AX
Connections - Terminals	Screw terminal

<b>Number Of Terminals</b>	2
<b>Rated Current</b>	16 AX at 250 V AC, inductive 16 A at 250 V AC, resistive
<b>[Ue] Rated Operational Voltage</b>	250 V AC
<b>Network Frequency</b>	50/60 Hz
<b>Connections - Terminals</b>	2 screw terminals
<b>Terminal Identifier</b>	L L1
<b>Tightening Torque</b>	0.4 N.m
<b>Clamping Connection Capacity</b>	2.5 mm <sup>2</sup> for rigid or stranded cable(s)
<b>Wire Stripping Length</b>	12 mm

## Environment

<b>Standards</b>	MS IEC 60669-1 IEC 60669-1 SS 227
<b>Ambient Air Temperature For Operation</b>	-5...40 °C
<b>Relative Humidity</b>	0...95 %
<b>Operating Altitude</b>	0...2000 m
<b>Environmental Characteristic</b>	Indoor use
<b>Ip Degree Of Protection IP20</b>	IP20

## Product Dimensions

Product Width	22.5 mm
Product Height	45 mm
Product Depth	33 mm
Embedding Depth	18 mm

## Packing Units

Number of units in Package 1	1 Pcs
Package 1 Width	75 mm
Package 1 Height	75 mm
Number of units in Package 2	20 Pcs
Package 2 Length	250 mm
Package 2 Width	88 mm
Package 2 Height	54 mm
Number of units in Package 3	200 Pcs
Package 3 Length	265 mm
Package 3 Width	196 mm
Package 3 Height	298 mm

## Contractual warranty

Warranty	5 years
----------	---------