



32A Double Pole Switch with led

Code: S5126

Main

Wiring Device Mounting	Flush Surface
Switch Function	2-Pole
Switch Application	Switch
Load Type	Incandescent lamp Resistive Inductive
Bulb Type Bulb Color	Led Red
Colour Tint	White, Beige, Champagne, Grey, Black

Complementary

Rated Current	32A 250V AC 50/60 Hz
Number of gangs	1 Gang
Material	PC (Polycarbonate): Frame Cover PC (Polycarbonate): Base PA6: Actuator Brass and copper alloy: terminals Silver alloy: contacts
Clamping Connection Capacity	1x23mm for solid cable(s) 1x23mm for stranded cable(s)
Connections - Terminals	Pillar terminals

Environment

Ambient Air Temperature For Operation	0....40°C
---------------------------------------	-----------

Relative Humidity	0....95%
-------------------	----------

Environmental Characteristic	Indoor use
------------------------------	------------

Standards	IEC 60669-1 BSEN60669-1
-----------	----------------------------

Product Dimensions

Product Height	80 mm
----------------	-------

Product Width	116 mm
---------------	--------

Product Depth	30 mm
---------------	-------

Embedding Depth	20 mm
-----------------	-------

Packing Units

Number of units in Package 1	1 Pcs
------------------------------	-------

Package 1 Width	85 mm
-----------------	-------

Package 1 Height	85 mm
------------------	-------

Number of units in Package 2	4 Pcs
------------------------------	-------

Package 2 Length	172 mm
------------------	--------

Package 2 Width	130 mm
-----------------	--------

Package 2 Height	90 mm
------------------	-------

Number of units in Package 3	40 Pcs
------------------------------	--------

Package 3 Length	474 mm
------------------	--------

Package 3 Width	274 mm
-----------------	--------

Package 3 Height	180 mm
------------------	--------

Contractual warranty

Warranty	5 years
----------	---------
