Product Datasheet





16A 2P+E Italian Socket-outlet with shutter

Code: S5627

Main

Product Or Component Type	Socket-outlet
Device Presentation	Mechanism with central plate
Device Mounting	Flush
Socket Number	1
Outlet Poles Configuration	2P+E
Outlet Standard	Italian
Outlet Standard Description	Centred earth
Rated Current	16 A
Colour Tint	White, Beige, Champagne, Grey, Black
Complementary	
Device Application	Power supply
Cover Type	With shutter
[Ue] Rated Operational Voltage	250 V
Network Type	AC
Network Frequency	50/60 Hz
Number Of Modules	1 module
Fixing Mode	Clip-in
Connections - Terminals	Screw terminals
Cable Cross Section	04 mm² cable(s), 2 - cable stiffness: flexible 04 mm² - cable stiffness: rigid
Minimum Load Breaking Capacity	100 operations 1.25 In and 1.1 Un, cos phi = 0.6
Electrical Durability	10000 cycles, cos phi = 0.8
Insulation Resistance	> 5 MOhm at 500 V
Dielectric Strength	2000 V

Material	PC (polycarbonate): cover PC (polycarbonate): base
Surface Finish	Glossy
Quantity Per Set	Set of 1 flow-pack
Standards	IEC 60884-1
Surface Treatment	Untreated
Resistance To Chemical Agents	Resistant to alcohol (70 %) Resistant to alcohol (96 %) Resistant to A-Lactic Acid Resistant to diluted quaternary ammonium Resistant to diluted bleach Resistant to diluted ammonia Resistant to soapy water Resistant to crystal cleaner Resistant to hydrogen peroxide 10 volumes Resistant to hexane
Environment	
Ambient Air Temperature For Operation	-535 °C
Ambient Air Temperature For Storage	-550°C
Ik Degree Of Protection	IK01
Ip Degree Of Protection	IP21D
Environmental Characteristic	Bleach Liquid soap Acetone Window-cleaning fluid Alcohol Petrol Oil UV resistant
Product Dimensions	
Product Width	22.5 mm
Product Height	45 mm
Product Depth	32.3 mm
Embedding Depth	21 mm

Packing Units

Number of units in Package 1	1 Pcs
Package 1 Width	75 mm
Package 1 Height	75 mm
Number of units in Package 2	20 Pcs
Package 2 Lenght	250 mm
Package 2 Width	88 mm
Package 2 Height	54 mm
Number of units in Package 3	200 Pcs
Package 3 Lenght	265 mm
Package 3 Width	196 mm
Package 3 Height	298 mm
Contractual warranty	
Warranty	5 years